

PERFEKT LIGHT



- Standard: 130lm/w (clear cover)
- Lumen Plus: 150lm/w (clear cover)
- Perfectly suitable for industrial use due to IP65
- High color fidelity through CRI 80Ra
- D-Mark tested for the use in paper production, wood processing etc.
- American market: UL, DLC Premium, cUL
- European market: TUV, GS, CB, CE (EMC, LVD, RoHS), D-Mark
- Australian market: SAA, C-Tick, RCM

Tomline(2017) Linear High Bay

2017-10

Lumen Plus :140~150lm/w (10 years warranty)

Model No.	Specification												
	Size	Rated Power	Input Voltage	LED Quantity	Color Temperature	Luminous flux	CRI	Materials	Beam Angle	IP Grade	Tomcarline driver		
T10B-100W	605*135*72mm	100W	AC100~277V 50~60Hz	196*1w EMC3030	3000K/4000K 5000K/6000K	14000LM	>70	Aluminum&PC Cover	120°	IP65	120H-42V		
T10B-150W	905*135*72mm	150W	AC100~277V 50~60Hz	252*1w EMC3030	3000K/4000K 5000K/6000K	21000LM	>70	Aluminum&PC Cover	120°	IP65	185H-42V		
T10B-200W	1205*135*72mm	200W	AC100~277V 50~60Hz	336*1w EMC3030	3000K/4000K 5000K/6000K	28000LM	>70	Aluminum&PC Cover	120°	IP65	240H-42V		

Standard: 120~130lm/w (5 years warranty)

Model No.	Specification												
	Size	Rated Power	Input Voltage	LED Quantity	Color Temperature	Luminous flux	CRI	Materials	Beam Angle	IP Grade	Tomcarline driver		
T10B-100W	605*135*72mm	120W	AC100~277V 50~60Hz	140*1w EMC3030	3000K/4000K 5000K/6000K	12500LM	>70	Aluminum&PC Cover	120°	IP65	120H-42V		
T10B-150W	905*135*72mm	150W	AC100~277V 50~60Hz	196*1w EMC3030	3000K/4000K 5000K/6000K	18500LM	>70	Aluminum&PC Cover	120°	IP65	185H-42V		
T10B-200W	1205*135*72mm	200W	AC100~277V 50~60Hz	252*1w EMC3030	3000K/4000K 5000K/6000K	25000LM	>70	Aluminum&PC Cover	120°	IP65	240H-42V		

Meanwell driver: 120~130lm/w (5 years warranty)

Model No.	Specification											EXW Price	
	Size	Rated Power	Input Voltage	LED Quantity	Color Temperature	Luminous flux	CRI	Materials	Beam Angle	IP Grade	Meanwell driver		
T10B-100W	605*135*72mm	120W	AC100~277V 50~60Hz	140*1w EMC3030	3000K/4000K 5000K/6000K	12500LM	>70	Aluminum&PC Cover	120°	IP65	ELG100-48A		
T10B-150W	905*135*72mm	150W	AC100~277V 50~60Hz	196*1w EMC3030	3000K/4000K 5000K/6000K	18500LM	>70	Aluminum&PC Cover	120°	IP65	ELG150-48A		
T10B-200W	1205*135*72mm	200W	AC100~277V 50~60Hz	252*1w EMC3030	3000K/4000K 5000K/6000K	25000LM	>70	Aluminum&PC Cover	120°	IP65	ELG240-48A		